

PRODUCT DESCRIPTION:

Our most effective, quickest acting floor stripper. It has been formulated with special odor-suppressing ingredients, making it a great choice for sensitive environments where odor is an issue. Its non-alkaline composition makes it truly a no-rinse product.

USES:

Strips off multiple coats of wax and finish. Ideal for use in schools, hospitals, office buildings etc.

ADVANTAGES:

Cuts through many layers of sealer and finish in minutes. No rinse is necessary when the residue is picked up with a wet vacuum. A tremendous time and labor saver. Noncorrosive, low foaming.

SPECIFICATIONS:

Active Ingredients: 45-50%pH: 11

Color: Clear

Solubility in Water: Complete Odor: Mild, Butyl

Flash Point: None

Viscosity: Water Thin Weight per Gallon: 8.26 Lbs.

PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.

PRODUCT USE

DILUTION RATE

Light Build-Up	8 oz. per gallon of cold water
Medium Build-Up	32 oz. per gallon of cold water
Heavy Build-Up	64 oz. per gallon of cold water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE PRODUCT DESIGNED FOR USE WITH COLD WATER

DIRECTIONS FOR PRODUCT USE:

FOR BEST RESULTS, USE OF WET-VAC IS RECOMMENDED

- 1. Dilute concentrate per the chart above based on the amount of build-up.
- 2. Apply to a small test area to determine the amount of time needed to adequately strip floor.
- 3. Mop diluted solution liberally onto floor surface working in 5' x 5' sections or use autoscrubber for application.
- Allow to stand 4-5 minutes. Keep area wet.
- 5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
- 6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
- 7. Allow floor to dry.
- Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

CAUTION: Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.

It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.



