

PRODUCT DESCRIPTION:

An extremely high quality floor finish formulated with metal cross linked polymers for added resilience.

USES:

Can be used on any floor not affected by water including resilient tile, composition tile and terrazzo as well as varnished, painted or sealed wood and masonry flooring.

ADVANTAGES:

Produces a very high gloss without buffing, resists scuffs, scratches and powdering. Slip resistant, fast drying, detergent resistant, and can be spray buffed or high speed burnished.

SPECIFICATIONS:

Total Solids: 25%

pH: 8.5

Color: Off White

Solubility in Water: Mixes

Odor: Mild

Flash Point: None Viscosity: Thin Liquid Weight per Gallon: 8.6 Lbs.

PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

SIZES AVAILABLE:

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.

DIRECTIONS FOR PRODUCT USE:

INITIAL APPLICATION

- 1. Remove all old wax and floor finish with appropriate stripper.
- 2. Rinse the floor thoroughly (at least twice) with clean water.
- 3. Repeat steps 1-2 if all old finish is not removed. Allow floor to dry.
- Apply 3-4 thin coats using a clean synthetic mop, allowing a minimum of 30 minutes between coats.
- Apply additional coats in same manner, allowing at least 30 minutes drying time between coats.
- For very porous floors, an initial coat of floor sealer is recommended.
 NOTE: Temperature, humidity and air movement affect curing time.
 To avoid contamination, do not return any used material to original container.

ROUTINE MAINTENANCE

- 1. Sweep or dust mop as necessary.
- 2. Damp mop with proper cleaner following label instructions. For accumulated soil, lightly scrub as needed.
- After cleaning, spray buffing or burnishing may also be done once loose dirt and dust has been swept up.
- 4. Additional coats may be applied if needed.

FOR PROPER PERFORMANCE USE ONLY WHEN PRODUCT TEMPERATURE AND FLOOR TEMPERATURE ARE 50° F or Higher.

WARNING: Do not allow wet floor areas to be open to foot traffic. Wet shoes or wet spots can create a slippery condition. Wet floor areas should be cordoned off until dry for traffic.

Coverage: 2000-2500 square feet per gallon



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

