



Stripping, Scrubbing, Carpet Care

The Hawk HD provides maximum power with the twin capacitor AC motor and Hawk's ruggedly reliable floor machine size. Both HD and XHD are powered by the 1.5 HP motor and offered with a wide range of tools, accessories and optional weights.

The optional DX package adds the 4 gallon solution tank, custom fit splash guard and premium pad driver.

Power

- 1.5 HP, 66 frame, dual capacitor AC motor.
- 115V, 60 Hz power, (230V optional)
- 50 ft. 12-3 SJT 2-Part (HD & XHD)
- **HD** uses triple-planetary HD 10:1 helical-cut commercial gears drive brushes and pads at 175 RPM.
- **XHD** (Extra Heavy Duty) planetary 11:1 helical-cut industrial gears, case hardened with steel coupler. drive brushes and pads at 165 RPM.

Engineered Design

- All steel construction with welded, powder-coated frame
- One piece, chromed heavy-duty steel handle with variable position lock and vinyl-dipped foam grips
- Powder-coated steel brush covers with full wraparound bumpers
- Dual steel operating triggers. Negative pressure on/off switch.
- Thumb-operated safety switch. 1" x 5" non-marking wheels.
- Optional frame weights (XHD only)

Safety Features

- Quiet 60dB (HD) and 66 dB (XHD) operation. Meets GS42 Standard.
- UL / CUL listed



HAWK HD

HAWK XHD



Welded Steel Frame, Handle and Brush Cover



XHD Machines Have 11:1 Ratio



DX Model Includes Pad Driver, Solution Tank & Splash Guard



Brush Covers in 7 Stock Colors Plus Chrome

Specifications HD

Specifications XHD

Model Part #	HP1513-HD F13-01	HP1515-HD F15-01	HP1517-HD F17-01	HP1520-HD F20-01	HP1513-XHD F23-01	HP1515-XHD F25-01	HP1517-XHD F27-01	HP1520-XHD F30-01
Machine Size	13 inch	15 inch	17 inch	20 inch	13 inch	15 inch	17 inch	20 inch
Pad Size	12 inch	14 inch	16 inch	19 inch	12 inch	14 inch	16 inch	19 inch
Pad Speed	175 RPM	175 RPM	175 RPM	175 RPM	165 RPM	165 RPM	165 RPM	165 RPM
Amp Draw	5.5 Amp	5.7 Amp	5.9 Amp	6.5 Amp	5.3 Amp	5.6 Amp	6.1 Amp	6.8 Amp
Weight	87 lbs.	91 lbs.	94 lbs.	97 lbs.	87 lbs.	90 lbs.	94 lbs.	99 lbs.
	ALL HD SIZES				ALL XHD SIZES			
Motor	1.5 HP, 66 frame, dual capacitor AC				1.5 HP, 66 frame, dual capacitor AC w/Chrome motor			
Drive System	Triple-planetary 10:1 helical-cut commercial gears				Triple-planetary XHD 11:1 helical-cut industrial gears			
Power Source	115-230V, 60 Hz (50 Hz optional)				115-230V, 60 Hz (50 Hz optional)			
Power Cord	50 FT, 12-3 SJT 2-Part (HD & XHD)				50 FT. 12-3 SJT 2-Part (HD & XHD)			
dB Rating	60 dB - Meets GS42 standard				66 dB - Meets GS42 standard			

Subject to Change Without Notice