

UNLOCK EXCEPTIONAL PERFORMANCE FOR DEMANDING INDUSTRIAL CLEANING APPLICATIONS.

Equipped with a powerful, latest-generation, die-cast aluminum squeegee, and a brush head with a 34 inch working path, the B 200 R Bp impresses with outstanding cleaning results. This scrubber has exceptional suction performance, setting a new benchmark in the industry with 50% less residual moisture left on the floors, which means the floors dry even faster. And it is also extremely easy and safe to use thanks in part to the large, color display and the patented KIK key system, which can help rule out operator errors. The scrubber also comes with the auto-fill function for quickly filling the 53 gallon freshwater tank, as well as the automatic tank rinsing system, which makes it convenient to clean the waste water tank. A daytime running light comes as standard for improved visibility and the B 200 R Bp has steel impact protection to protect against damage.









1 Simple controls and LCD displays

- Single dial to select mode of operation is intuitive and makes for easy training.
- Check power, pump, brush motor, vacuum motor, and reverse operation at a glance.
- Screen displays machine status, fault alerts, and service intervals.

2 Outstanding Suction Performance

- The suction performance sets a new benchmark-50% less residual moisture on industrial floors.
- Tear-resistant, long-lasting Linatex* squeegee blades for excellent drying results.
- Fast and simple tool-free replacement of the blades.
- Parabolic design helps channel water to the recovery point.

3 Newly developed roller brush deck

- New aluminum die cast roller brush head provides industrial strength and reduced decibel level (approx. -10dB(A)).
- Rollers can be changed in a matter of seconds without tools.
- Roller brush provides excellent cleaning results with 7 times the contact pressure compared to disc technology.

4 Safety and durablity comes standard

- The scrubber is equipped with a daytime running light which ensures a safer cleaning experience, especially in low-light environments.
- This scrubber comes with steel impact protection, providing robust durability and safeguarding against potential damage.

Technical data and equipment.









	B 200 R BP SIDE BROO	 B 200 R BP + R85	;	B 200 R BP + D90	B 200 R BP + D110
TECHNICAL SPECIFICATIONS					
Cleaning path/width	in 34	34	;	35	43
Brush type	Cylindrical	Cylindrical	1	Disc	Disc
Brush Quantity	nits 2	2	:	2	2
Brush Diameter	in 33	33		35	43
Suction bar (squeegee) width	in 46	46		46	46
Drive	Traction	Traction		Traction	Traction
Solution/recovery capacity	gal 53/53	53/53	!	53/53	53/53
Theorical/practical productivity sq.	t /hr 58,125	58,125		58,125	58,125
Operating noise level	IBA 67	67	(67	67
Battery charger	Shelf	Shelf		Shelf	Shelf
Brush contact pressure	Ibs 207	207	:	207	207
Brush speed	rpm 180-1300	180-1300		180-1300	180-1300
Drive/ vac motor rating	atts 2500	2500	:	2500	2500
Weight without batteries	Ibs 2,191	2,191		2,191	2,191
Dimensions (LxWxH)	in 75x42x56	75x42x56		75x42x56	75x42x56
Minimum turning radius	ft 2.9	2.9	:	2.9	2.9
Climbing ability - maximum slope % g	ade 10	10		10	10
Max. working speed working	nph 3.7	3.7	:	3.7	3.7

EQUIPMENT

Order No.	Description
9.200-056.0	B 200 R Bp 2SB R 85 cylindrical scrub deck, 36V/312 Ah AGM batteries
9.200-055.0	B 200 R Bp 2SB R 85 cylindrical scrub deck, 36V/360 Ah batteries
9.200-054.0	B 200 R Bp R 85 cylindrical scrub deck, 36V/312 Ah AGM batteries
9.200-053.0	B 200 R Bp R 85 cylindrical scrub deck, 36V/360 Ah batteries
9.200-057.0	B 200 R Bp D 90 scrub deck, 36V/312 Ah AGM batteries
9.200-058.0	B 200 R Bp D110 scrub deck, 36V/312 Ah AGM batteries

ACCESSORIES

AC	CESSORIES	
	Order No.	Description
•	4.778-009.0	Suction bar parabolic 1180mm/46in
•	2.763-048.0	Brush-head R 85 (Depending on model selected)
	2.763-008.0	Brush-head D 90 S (Depending on model selected)
	4.035-513.0	Cover tank flushing system complete
	4.039-363.0	Suction lip set PU 1180mm/46in
	4.039-362.0	Suction lip set Linatex® 1180mm/46in
	8.629-184.0	Battery AGM 6V 285AH (C5) / 330AH (C20)
	8.622-842.0	Battery, 6V, 360AH (J305H-AC)
	8.600-015.0	Battery charger
	8.641-489.0	Charger, 36V 21A SB175 ALG 7
	2.644-225.0	Add-on kit deflector roll stackable
	2.642-058.0	Add-on kit spray sucking B150R
	4.444-015.0	Suction hose accessories, for taking in water from corners (e.g. deep freezers)
	4.039-355.0	RM tank completely 5 L. Only suitable for compatible scrubber dryers with Dose cleaning agent dosing system.
	4.035-516.0	360° Warning Beacon (field installation required)

■ Included □ Optional

Please contact us for more information:

Kärcher U.S.A.

6398 N. Kärcher Way Aurora, CO 80019 U.S.A.

Tel. 888-805-9852 Fax 800-248-8409











