



NSS Enterprises, Inc.

## 20-INCH ULTRA HIGH-SPEED BURNISHER

# CHARGER 2500

The Charger 2500 brings marble and terrazzo floors back to a high-gloss shine. Ideal for use in high-speed maintenance programs to bring back the shine after damp mopping or scrubbing.

- Simple to use. The adjustable wheel in the front of the machine sets the pad pressure. A color-coded meter on the top of the motor cover keeps the operator aware of the pad pressure at all times.
- Maneuverable. A well-balanced pad driver provides smooth operation, making the Charger 2500 easy to control in open areas and narrow hallways.
- Safe for your operators and the facility. The Charger 2500 is equipped with a mechanical safety switch to prevent accidental starts, a high-visibility yellow power cord and a soft bumper to protect walls and furniture from damage.



**DO NO HARM™**

Smooth operation, angled hand grips, and an adjustable handle put your operator in the right position to use the Charger 2500 for hours without stressing their back and wrists.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

## SPECIFICATIONS

# CHARGER 2500

<b>Pad Speed</b>	2500 RPM
<b>Pad Size</b>	20 in (51 cm)
<b>Pad Driver</b>	20 in (51 cm) flexible
<b>Motor</b>	
Type	DC dual-rectified permanent magnet
Frame Size	66
Voltage	120V or 240V
HP	1.5 (1120 Watts)
RPM	2500
<b>Current</b>	12A @ 120V or 6A @ 240V
<b>Overload Protection</b>	17A circuit breaker (120V) 8A circuit breaker (240V)
<b>Drive</b>	Direct
<b>Construction</b>	Powder coated cast aluminum
<b>Wheels</b>	5 in (13 cm) non-marking rubber
<b>Handle</b>	1.5 in steel tube
<b>Sound Level</b>	63 dBA
<b>Safety Switch</b>	Mechanical lock-out switch
<b>Cord Length</b>	75 ft (15 m)
<b>Cord Type</b>	14-3 ST Yellow
<b>Dimensions L x W x H</b>	30 x 23 x 38 inches 76 x 59 x 97 cm
<b>Machine Weight</b>	87 lbs (39 kg)
<b>Shipping Weight</b>	112 lbs (51 kg)
<b>Shipping Class</b>	125
<b>Warranty</b>	7 years parts, 1 years labor
<b>Productivity</b>	9,545 ft <sup>2</sup> /hr (887 m <sup>2</sup> /hr)



1. Mechanical lock-out prevents accidental starts and unauthorized use.
2. Heavy-duty metal cord strain relief protects the 75 foot safety yellow cord.
3. The 66-frame, 1.5 HP motor provides long life and aggressive burnishing.
4. Precise pressure can be controlled with the pad adjustment knob.
5. The easy-to-read, color-coded pad pressure meter provides feedback to the operator.
6. The handle height adjusts to the operator's preferred height.
7. The powder-coated cast-aluminum base withstands tough conditions.
8. The flexiwall shield and brush controls dust and protects the cord from the pad driver.
9. The non-marking bumper protects walls and furniture from accidental bumps.



### NSS ENTERPRISES, INC.

3115 Frenchmens Road  
Toledo, OH 43607-2958  
USA

(800) 677-1663 **TEL**  
(419) 531-3761 **FAX**  
info@nss.com

### OPTIONS AND ACCESSORIES

#### ECOSTRIP



Ecostrip Buff pads have a fine 8500 grit diamond coating that brings back the shine after scrubbing. Perfect for high traffic areas and light restoration work.

**NSS.COM**