



NSS Enterprises, Inc.

WET/DRY VACUUMS

COLT

Demanding jobs require durable and versatile equipment. Whether cleaning up a job site, stripping floors or dealing with flooded areas, Colt Wet/Dry Vacuums can get the job done.

- Three models available:
 - Colt 1450 P - A large capacity vacuum with a highly durable polyethylene tank.
 - Colt 1250 S - A mid-sized vacuum with a stainless steel tank. For applications that need thorough tank cleaning, like healthcare.
 - Colt 1050 P - A small polyethylene tank wet/dry vacuum with big vacuum power.
- Tip disposal feature. Colt 1250 S and Colt 1450 P vacuums have a pivot on the base allowing them to be dumped into any drain, up to toilet height.
- Optional front mount squeegee. Colts are available with a 27-inch straight squeegee to boost productivity in large-area wet pick-up.



COLT 1450 P WITH SQUEEGEE



COLT 1250 S WITH SQUEEGEE



COLT 1050 P WITH SQUEEGEE



The front mount squeegee helps reduce operator fatigue often associated with using a hose and wand. At 62 dbA, Colts can be used for daytime cleaning.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

COLT

Input Voltage	100-120V, 60 Hz or 220-240V 50/60 Hz		
Motor Type	2-stage bypass		
Power	1.23 HP (920 Watts)		
Airflow	92 CFM (2.6 m ³)		
Water lift	84 inches (213 cm)		
Tank Construction	1450 P / 1050 P Polyethylene	1250 S Stainless Steel	
Capacity	1050 P 10.5 Gal (40 L)	1250 S 12.5 Gal (47 L)	1450 P 14.5 Gal (55 L)
Tool Kit	Sold Separately		
Filter Area	625 in ² (0.4 m ²)		
Cord	35 ft (9 m) 18-3 SJT		
Sound Level	62 dbA		
Dimensions	L	W	H
1050 P	29 in (73 cm)	19 in (48 cm)	29 in (73 cm)
1250 S	31 in (79 cm)	23 in (58 cm)	40 in (101 cm)
1450 P	31 in (79 cm)	23 in (58 cm)	40 in (101 cm)
Weights	1050 P	1250 S	1450 P
Machine	48 lbs (21 kg)	63 lbs (39 kg)	62 lbs (38 kg)
Shipping	67 lbs (24 kg)	90 lbs (41 kg)	89 lbs (40 kg)
Shipping Class	150		
Warranty	3 years parts, 1 year labor, 10 years on rotomolded parts		



1. High air intake; float shut off activates long before any moisture reaches the vacuum motor.
2. The cone surrounding the float shut-off combines with the round tank to generate cyclonic action, forcing liquid and debris to the sides and bottom of the recovery tank and away from the vacuum motor.
3. Optional HEPA filter assembly available. Capture 99.97% of particles at 0.3 microns. Filter area 1,770 square inches.
4. Optional 27-in front mount squeegee increases productivity by allowing quick wet recovery over large floor areas.
5. Large chemical-resistant rear wheels and front casters make the Colt extremely maneuverable.
6. Colt power heads are free standing. Set them on the floor and run them to circulate air through the internal chambers, completely drying them after every use.
7. Tip-dispose tank allows easy emptying into most toilets and drains. (1250 S and 1450 P models)

TOOL KITS (SOLD SEPARATELY)

Colt tool kits are constructed with high-quality NSS parts: brass fittings, cast aluminum tools, steel wands and durable 10-ft superflex hoses. There are NSS tool kits for any application, wet or dry, and any surface, hard or soft.



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

NSS.COM