



NSS Enterprises, Inc.

TILE AND GROUT RESTORATION MACHINE

RALLY 1200

Clean bathrooms eliminate the opportunity for complaints and create an overall feeling of trust with your company or institution. To completely manage the soil and bacteria that build up in bathrooms, grout cleaning is a must. The Rally 1200 gives you the ability to maintain new tile and improve neglected tile and grout to a like-new condition.

- The Rally 1200's Hard Surface Tool uses two streams of 1200 PSI water to turn the spray bar at up to 1400 RPM. This high pressure spray helps remove soil from the tile and grout. A vacuum shroud surrounding the tool pulls the dirty water into the recovery tank.
- Continuous water supply keeps your staff productive on large jobs. Use standard garden hoses to supply water to and drain water from the Rally 1200.
- Not just for hard floors. Reduce the pressure on the Rally 1200 and it can be used as a cold water carpet extractor.
- Easy maintenance. By removing a single bolt, the tanks on the Rally 1200 can be tilted back, revealing the inner workings of the machine.



Rally 1200 with Hard Surface Tool

DO NO HARM™

Restore neglected tile rather than replacing it. With the right combination of chemicals and tools, the Rally 1200 can help you restore tile and grout, avoiding the expense and environmental impact of replacement.

Printed on Green Seal® certified paper that contains 30% recycled post-consumer fiber.

SPECIFICATIONS

RALLY 1200

Solution Tank	12 Gallons (45 L)
Recovery Tank	12 Gallons (45 L)
Solution Pump	Adjustable, 400 - 1200 PSI
Accessory Valve	Quick disconnect, all brass
Vacuum Motor	2-stage, 2.1 HP (1565 Watts)
Water Lift	140 inches (355 cm)
Hoses	25 ft (7.6 m)
Input Voltage	120V or 240V
Construction	
Tanks	Rotomolded polyethylene
Wheels	Two 10-in (25 cm)
Casters	Two 4-in (10 cm)
Cord	Two 25 ft (7.6 m) 12-3 SJTW
Sound Level	75 dBA
Dimensions	
L x W x H	39 x 26 x 17 inches 99 x 66 x 43 cm
Weight	150 lbs (68 kg)
Warranty	1 year parts, 10 years on tanks.
Productivity	500 ft ² /hr (47 m ² /hr)



1. Circuit detector helps ensure the heated extractors don't overload the building circuits
2. Built-in bleed valve allows quick disconnecting and reattaching of tools by releasing the water pressure.
3. Attach garden hoses to supply and dump water continuously during use.
4. Durable 12 gallon tanks won't rust or corrode and have a 10 year warranty.
5. Wheel on the handle assists loading the machine into trucks
6. Quick release cord wraps.
7. A 45° elbow on the drain helps divert dirty water into sinks and toilets.



15" Hard Surface Tool
Spray Bar



NSS ENTERPRISES, INC.

3115 Frenchmens Road
Toledo, OH 43607-2958
USA

(800) 677-1663 **TEL**
(419) 531-3761 **FAX**
info@nss.com

OPTIONS AND ACCESSORIES



Hydroglide 2 Wand - This next-generation carpet wand uses a durable Delrin glide to reduce drag for smooth operation on any surface. Reduce operator fatigue and increase the extraction of soil and moisture from carpet. The rugged polyethylene wand head with tear drop design efficiently collects dirty water. The wand is manufactured with 1.5" aircraft aluminum alloy tubing and only weighs 6.4 pounds.



Two-Jet Stainless
Steel Wand



30" Stair Tool.



4" Upholstery Tool

NSS.COM