

## **PRODUCT DESCRIPTION:**

A non-corrosive, rinseless, mop-on stripper formulated to immediately rip off multiple layers of finish or sealer using cold or warm water.

#### **USES:**

Strips off multiple coats of wax and finish without the use of a floor machine and stripping pad.

#### ADVANTAGES:

Cuts through many layers of sealer and finish in minutes. No rinse is necessary when the residue is picked up with a wet vacuum. A tremendous time and labor saver. Noncorrosive.

## **SPECIFICATIONS:**

**Active Ingredients: 70%** 

pH: 12 Color: Blue

Solubility in Water: Complete

**Odor: Lemon** Flash Point: None **Viscosity: Water Thin** Weight per Gallon: 8.1 Lbs.

## PRODUCT/CONTAINER DISPOSAL:

Dispose of used/unwanted product according to state and local regulations. Offer container for recycling.

## **SIZES AVAILABLE:**

1 Gallon Bottle, 5 Gallon Pail, 30 & 55 Gallon Drums.

### **PRODUCT USE**

# **DILUTION RATE**

Light Build-Up	8 oz. per gallon of cold or warm water
Medium Build-Up	32 oz. per gallon of cold or warm water
Heavy Build-Up	64 oz. per gallon of cold or warm water

DILUTION MAY VARY BASED ON BUILD-UP OF OLD FINISH ON FLOOR SURFACE PRODUCT DESIGNED FOR USE WITH WARM WATER

#### **DIRECTIONS FOR PRODUCT USE:**

FOR BEST RESULTS, USE OF WET-VAC IS RECOMMENDED

- 1. Dilute concentrate per the chart above based on the amount of build-up. Apply to a small test area to determine the amount of time needed
- to adequately strip floor. Mop diluted solution liberally onto floor surface working in 5' x 5'
- sections or use autoscrubber for application.
- Allow to stand 4-5 minutes. Keep area wet.
- 5. If surface is unusually dirty or scuffed, use mop, brush or floor machine to agitate and loosen dirt and finish; for stubborn marks scrub using a stripping pad.
- 6. Pick up solution with a mop or wet-vac machine. No rinsing required if a wet-vac is used.
- 7. Allow floor to dry.

information.

Apply first coat of finish or floor sealer in full uniform coat. Apply additional coats of floor finish as required.

CAUTION: Never allow solution to dry on floor. Always test solution on an inconspicuous area of floor to be stripped to check compatibility. Emulsified floor finish and wax are very slippery; keep area clear until surface is completely dry.



It is recommended that protective gloves and safety glasses be worn when using this and all cleaning products.

