



REINVENT HOW THE WORLD CLEANS

# T291

## Small walk-behind scrubber

### Big value in a small size

Get a lot of value in a small scrubber with intuitive controls, comfortable ergonomics, and straight-forward operation. Daily maintenance is made easy due to a large recovery tank lid opening, no-tool brush/pad replacement, and yellow touchpoints. Perfect for facility owners and operators who want a productive, easy-to-use machine that is also easy to maintain.

### Available technologies



ec-H2O NanoClean® with Severe Environment™ technology



Lithium-ion technology



### Comfortable & easy to maneuver

Optimize operator comfort with great maneuverability and an adjustable handle with comfortable grip for ergonomic operation.



### Easy operation

Operate with ease and simplify operator training using pre-programmed cleaning settings.



### Extend cleaning uptime

Reduce noise levels and water consumption while increasing run time with ECO mode.

# Inside the T291

- 1. Self-leveling brush technology** for optimum cleaning performance on various surfaces.
- 2. Intuitive controls** featuring pre-programmed cleaning settings, standard and ECO mode, make it easy to operate and train.
- 3. Large LCD display** with clear controls and multilingual support allows users to monitor helpful information.
- 4. Large sized recovery tank opening** enables full access and visibility to help simplify daily maintenance.
- 5. Effective squeegee design** and standard Linatex® blades offer excellent water pick-up.
- 6. No-tool brush/pad change system** simplifies maintenance with the ability to spin-on and spin-off from the operator controls.
- 7. Yellow touch points** help simplify operator training and daily preventative maintenance.
- 8. On-board charger** allows for flexible charging.



## T291 specifications

FEATURE	SPECIFICATION	
Drive System	Pad-assist	Self-propel
Cleaning path	20 in / 500 mm	20 in / 500 mm
Productivity (per hour) theoretical max	21,173 ft <sup>2</sup> /h / 1,967 m <sup>2</sup> /hr	26,565 ft <sup>2</sup> /h / 2,468 m <sup>2</sup> /h
Max Speed	NA	3.4 mph
Scrub head raise/lower		Manual
Brush/Pad Speed		150 rpm
Brush Down Pressure		40 lbs / 18.1 kg
Solution Tank		13.2 gal / 50 L
Recovery Tank		13.2 gal / 50 L
System Voltage		24 Volt
Battery run time - (up-to hours)*	L-ion: 2.5 hrs   Wet: 3.2 hrs   AGM: 3.7 hrs	L-ion: 2.0 hrs   Wet: 3 hrs   AGM: 3.5 hrs
Dimensions (L x W x H)	52.2 x 33.2 x 40.7 in / 1,326 x 843 x 1,034 mm	
Squeegee width	30.4 in / 772 mm	
Weight (with battery)	373 lbs / 169 kg	390 lbs / 40.9 kg
Sound level (dBA)**	ECO Mode: 63 dBA   Standard: 66 dBA	
Conventional	Standard	
ec-H2O NanoClean® technology	Optional	
Severe Environment™ technology	Standard with ec-H2O NanoClean® technology	

Specifications subject to change without notice.

\* Run times are based on Continuous Scrubbing Run Times.

\*\* Sound levels per ISO 11201 as recommended by the American Association of Cleaning Equipment Manufacturers & OSHA

For a demonstration or additional information, call **+1.800.553.8033** or email **info@tennantco.com**

t291-brochure-en-noam 3/25 ©2025 The Tennant Company.

LINATEX and the Linatex red color are trademarks and/or registered trademarks in the name of Linatex Ltd, a Weir Group PLC company. Tennant Company's products are sold and serviced through subsidiaries of Tennant Company and distributors. All rights reserved.

**Tennant Company**  
 10400 Clean Street  
 Eden Prairie, MN 55344-2650, USA  
 USA/Canada: +1.800.553.8033  
 Quebec: +1.800.361.9050  
 Overseas: +1.763.540.1315  
[www.tennantco.com](http://www.tennantco.com)