

# T7 Micro-Rider Floor Scrubber

## Easy Operation & Maintenance

Clean both large areas and tight spaces easily with a floor scrubber designed for greater efficiency and less environmental impact.

## Available Technologies



ec-H2O NanoClean®



IRIS® Asset  
Manager



**Easily train** new operators to use the simple, intuitive controls.



**Leave behind no cleaning solution** even around 180-degree turns, with the T7's equal-pressure, parabolic squeegee.



**"No hassle" squeegee system**, there are no tools for maintenance and the blade is factory set at the optimum recovery angle.

# More T7 Features

1. **Exclusive Hygenic<sup>®</sup> solution and recovery tanks** are fully accessible for easy cleaning.
2. **Decrease the chance of accidents** with automatic braking and parking brake actuation.
3. **Quickly** remove and replace brushes and squeegees.



## T7 Specifications

| FEATURE                                          | SPECIFICATION                                 |                                                |
|--------------------------------------------------|-----------------------------------------------|------------------------------------------------|
|                                                  | 26 in/660 mm                                  | 32 in/810 mm                                   |
| Productivity (per hour) Theoretical Max          | 45,760 ft <sup>2</sup> / 4,250 m <sup>2</sup> | 56,320 ft <sup>2</sup> / 5,230 m <sup>2</sup>  |
| Estimated Coverage* Conventional                 | 23,760 ft <sup>2</sup> / 2,210 m <sup>2</sup> | 29,700 ft <sup>2</sup> / 2,760 m <sup>2</sup>  |
| Estimated Coverage*ec-H2O NanoClean <sup>®</sup> | 31,680 ft <sup>2</sup> / 2,950 m <sup>2</sup> | 39,600 ft <sup>2</sup> / 3,680 m <sup>2</sup>  |
| Brush motor                                      | .6 hp / 0.45 kW                               |                                                |
| Brush/pad RPM                                    | 225 rpm                                       |                                                |
| Brush/pad pressure                               | 80, 120, 160 lb / 36, 54, 73 kg               |                                                |
| Solution tank capacity                           | 29 gal / 110 L                                |                                                |
| Recovery tank capacity                           | 29 gal / 110 L                                |                                                |
| Vacuum motor                                     | 0.6 hp / 0.45 kW                              |                                                |
| Vacuum waterlift                                 | 70 in / 1,780 mm                              |                                                |
| System voltage                                   | 24 volt                                       |                                                |
| Battery run time (up to hours)**                 | 3.0                                           |                                                |
| Length x width x height                          | 60 x 33.25 x 50 in<br>1,520 x 850 x 1,270 mm  | 60 x 39.25 x 50 in<br>1,520 x 1,000 x 1,270 mm |
| Weight (with Batteries)                          | 850 lb / 386 kg                               |                                                |
| Sound level (operator's ear)***                  | 67 dBA                                        |                                                |

*Specifications subject to change without notice and will vary throughout the operation of the machine; averages are shown.*

For a demonstration or additional information,  
call **+1.800.553.8033** or email **info@tennantco.com**